

2510-5

25x25x10mm (0.98x0.98x0.39 in) - 5 blade



- Bearing System ----- 2 Ball Bearing,
- Life Expectancy ----- 100000hrs @ 10000RPM @ 30C
- Frame----- Thermoplastic PBT+30% GF, UL94-V0
- Impeller----- Thermoplastic PBT+15% GF, UL94-V0
- Lead Wire----- UL 1061, AWG 30, 240 ± 10mm, Red(+), Black(-)
- Protection----- Locked rotor protection
- IP Grade ----- IP51, IP54



IATF16949:2016
ISO 9001:2015
ISO 14001:2015



Dim: 494x423x155 mm
N.W.: 8.2 kgs
G.W.: 10.7 kgs
Q' TY: 1080 pcs

FUNCTIONS	PART NUMBER	RATED (VDC)	LABEL CURRENT	ACTUAL CURRENT	POWER (WATTS)	SPEED (RPM)	AIRFLOW (CFM)(m³/min)		PRESSURE (mmAq)(In H²O)		NOISE (dBA)	WEIGHT (Q'TY/CTN)
1b:AS 2a:FG	D2510H05BPLBxy-5	05 (04~06)	0.260	0.220	1.10	13000	2.60	0.07	6.67	0.26	30.54	7.6g (1080pcs)
	D2510M05BPLBxy-5		0.190	0.190	0.95	10000	2.02	0.06	4.05	0.16	24.21	
	D2510L05BPLBxy-5		0.140	0.140	0.70	7000	1.39	0.04	1.98	0.08	18.14	
	D2510X12BPLBxy-5	12 (07~14)	0.136	0.130	1.56	15000	2.92	0.08	8.00	0.32	34.19	7.6g (1080pcs)
	D2510H12BPLBxy-5		0.090	0.090	1.08	13000	2.60	0.07	6.67	0.26	30.54	
	D2510M12BPLBxy-5		0.070	0.070	0.84	10000	2.02	0.06	4.05	0.16	24.21	
	D2510L12BPLBxv-5		0.060	0.060	0.72	7000	1.39	0.04	1.98	0.08	18.14	

Remark:

1. Part no. suffix: "xy" =Function detail or "x" =Function number. and "y" =customer ID
2. D series - High Performance series:

Uses single coil differential type drive with higher efficiency and more functions (depending on the specific model).

